

BAG SPECIFICATION

Product Code	XL6SL3	
Product Description	55-Gallon, Standard Barrier, Aseptic Bag	
Irradiation	Minimal dose: 1.5Mrad	
Bag Inner Dimensions	1560 mm length, 890 mm width	61 3/8" length, 35" width
Oxygen Transmission	<1.0 cc/m ² /day (at 23°C 0% RH)	<0.0645 cc/100 in ² /day (at 73.4°F 0% RH)
Tolerances	Length ± 25 mm , Other ± 15 mm	Length ± 1" , Other ± 5/8"

	STRUCTURE	MATERIAL	THICKNESS	
Outer Ply		PE / Met PET / PE Metal	102 μ	4 Mil
Middle Ply		LLDPE Transparent	50 μ	2 Mil
Inner Ply		LLDPE Transparent	50 μ	2 Mil
SPOUT CAP		MDPE - Grey PA (Nylon)- Dark Blue	1 inch, Plug type	

All raw materials are Food Contact approved and comply with the FDA applicable requirement of title 21 of the Federal Regulation Code, & comply with EU directive 10/2011 + 90/128/EEC + 1935/2004 + (EC) №2023/2006.

	Dimensions	mm	inch
		A	1560
B		890	35
C		445	17 1/2
D		65	2 1/2

Packaging	32 bags in a carton box	36 Boxes per Pallet	1152 bags per Pallet
	Box Dimensions:	575mm x 475mm x 190mm	22 5/8" x 18 3/4" x 7 1/2" h
Weight	Bag	0.559Kg	1.23lb
	Box	19.45Kg	42.9lb
	Pallet	719Kg	1586lb
Version	July 14, 2021	Ref :	5150550002